


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index No. E-13

History of original corner establishment:

This corner was originally established by Frank W. Campbell under Contract No. 521 dated January 8, 1885. The notes state that at the corner a 12" x 12" x 2" notched basalt stone was set from which:
 A 24" pine bears N 28° E, 107 Lks (70.6 feet) marked T7S R27E S3BT
 A 7" pine bears S 80° E, 175 Lks (115.5 feet) marked T7S R27E S10BT
 A 24" pine bears S 35° W, 139 Lks (91.7 feet) marked T7S R27E S9BT
 A 30" pine bears N 20° W, 156 Lks (103.0 feet) marked T7S R27E S4BT



No record of subsequent remonumentation found in County Records .

Description of corner evidence found:

The original stone was not recovered. The corner position was re-established from the average of record distance measurements from each of the original BT's. From the re-established corner position:
 A 17" pine snag stump bears N 32° E, 72.3 feet scribed T7S R -- E
 A 17" pine (healthy with healed blaze) bears S 71° E, 118.4 feet
 A 20" pine stump bears S 36½° W, 92.6 feet, tree is laying beside stump scribed T7S R27E --
 A 30" dead pine bears N 22½° W, 104.5 feet scribed T7 R27 S4
 Note: Original record distances to the BT's were very poor. The distances from northeast and southwest BT's did not intersect by 3 feet +. The distances from the northwest and southeast BT's did not intersect by 6 feet +. Corner was re-established at average position considering all four original BT's.

Description of monument and accessories established to perpetuate the original location of this corner


At the corner position a 2 inch by 30 inch iron pipe, with brass cap marked as shown, was set 4 inches in the ground and surrounded with a mound of stones to the cap.
 Set steel fence post east of corner and attached signs 54-2 and 54-4.
 Established 3 new BT's: (17" original BT in southeast quadrant re-used)
 An 8½" pine bears N 24° E, 53.8 feet scribed T7S R27E S3BT
 A 6½" juniper bears S 25° W, 81.5 feet scribed T7S R27E S9BT
 A 6" juniper bears N 75° W, 16.6 feet scribed T7S R27E S4BT
 New BT's have a lower blaze scribed BT with brass washer stamped PLS 1106 nailed flush.
 Attached signs 54-3 and 54-4 to all BT's and painted red ring around the trees above the upper blaze.

Used steel tape and magnetic compass with 19½° east declination. Measured to center of Bts.
 See map of survey.

This corner set September 20, 1979.

Witnesses: D. Kaufman, PLS
 G. Flowers, LSIT
 B. English
 B. Reynolds

REGISTERED PROFESSIONAL LAND SURVEYOR <i>William R. Wells</i> OREGON JULY 22, 1977 WILLIAM R. WELLS 1106



Office of County Surveyor County of Grant
 State of Oregon, I hereby certify that the within Instrument was filed in this office
 for record on the 15 day of Oct 1979.
Edward Baggett by _____
 (COUNTY OFFICIAL) (DEPUTY)