


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index No. J-21

History of original corner establishment:

This corner was originally established by Frank W. Campbell under Contract No. 521 dated January 8, 1885. The notes state that at the corner a 10" x 10" x 7" notched basalt stone was set 7" in the ground from which:

- A 30" pine bears N 20° E, 55 Lks (36.3 feet) marked T7S R27E S12BT
 - A 10" pine bears S 48° E, 95 Lks (62.7 feet) Marked T7S R27E S13BT
 - A 12" pine bears S 7° W, 82 Lks (54.1 feet) marked T7S R27E S14BT
- No other trees were within limits and a mound of stone was raised alongside corner.



No record of subsequent remonumentation found in County Records .

Description of corner evidence found:

Original stone and mound was not recovered. A jeep road bears North 6 feet ±.
 Re-established corner position from the original BT's. From the re-established corner position:
 A 19½" pine bears S 48° E, 62.7 feet scribed 7S R27E S13 (tree's top is broken out).
 A 15" pine stump, 4½ feet tall, bears S 6° W, 54.1 feet scribed 7E S14.
 Remains of rotted stump hole bear N 22° E 36.3 feet, There are traces of scribing on the tree to the stump hole. Tree has slid down hill 6 to 8 feet. The scribing appears to have been X-ed out, i.e. X X


Description of monument and accessories established to perpetuate the original location of this corner

At the corner position a 2 inch by 30 inch iron pipe, with brass cap marked as shown, was set 6 inches in the ground and surrounded with a mound of stones to the cap.
 Set steel fence post east of corner and attached signs 54-2 and 54-4.
 Established 4 new BT's:
 An 8½" juniper bears N 10½° E, 37.9 feet scribed T7S R27E S12BT
 An 11" school-marm juniper bears S 81½° E, 15.0 feet scribed T7S R27E S13BT (measured from center of root crown. This tree has a blaze head high).
 An 18" red fir bears S 30½° W, 96.6 feet scribed T7S R27E S14BT
 A 10" red fir bears N 57½° W, 92.7 feet scribed T7S R27E S11BT
 New BT's have a lower blaze scribed BT with brass washer stamped PLS 1106 nailed flush.
 Attached signs 54-3 and 54-4 to all BT's and painted red ring around the trees above the upper blaze.
 Used steel tape and magnetic compass with 19½° east declination. Measured to center of Bts.
 See map of survey.

This corner set September 11, 1979

Witnesses: G. Flowers, LSIT
 B. Reynolds

REGISTERED PROFESSIONAL LAND SURVEYOR
<i>William R. Wells</i>
OREGON JULY 22, 1977 WILLIAM R. WELLS 1106



Office of County Surveyor County of Grant
 State of Oregon, I hereby certify that the within Instrument was filed in this office
 for record on the 15 day of Oct 1979
Robert D. Engert by _____
 (COUNTY OFFICIAL) (DEPUTY)