


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Refer to: Plat of Wilson 1985 Cadastral Survey  
Section 29, T.7S., R.27E., W.M.

History of original corner establishment:

No record of previous monumentation.



Description of corner evidence found:

None.

Description of monument and accessories established to perpetuate the original location of this corner:

At the corner point I set a 2 1/2" X 30" alum. pipe with a 3" alum. cap containing a magnet and marked:

I built a stone mound around the monument.

S29  
C-S-SW-NE  
1/256  
PLS 1832  
1986

From the corner:

- A Ponderosa Pine, 7" dia., N84 1/2°E, 27.0 ft.  
marked: C S SW NE 1/256 S29 BT
- A Ponderosa Pine, 8" dia., N21 1/4°E, 24.2 ft.  
marked: X at breast height and BT at base.
- A Ponderosa Pine, 12" dia., N53°E, 33.3 ft.  
marked: C S SW NE 1/256 S29 BT
- A Ponderosa Pine, 12" dia., N8°W, 27.3 ft.  
marked: C S SW NE 1/256 S29 BT

BTs have blaze and a 6" stripe painted red, a BT tag, a "Land Survey Monument" sign and an alum. "PLS 1832" washer nailed to the bottom of the blaze. There is a 6' steel fence post with a "Land Survey Monument" sign within 5' of the corner.

Measured to center of BTs using steel tape and staff compass. Magnetic declination set at 18°E.

April 13, 1986 // July 1, 1986 add BTs.

Office of.....*Larimer*..... County of.....*Grant*.....  
State of.....*Oregon*..... I hereby certify that the within instrument was filed in this office  
for record on the.....*25* day of.....*July*....., 19.....*86*  
*Robert O. Dejeu* by.....  
(COUNTY OFFICIAL) (DEPUTY)

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Fayette S. Munro*

OREGON  
JULY 13, 1979  
FAYETTE S. MUNRO  
1832