

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Refer to: Plat of Wilson 1985 Cadastral Survey
Section 29, T.7S., R.27E., W.M.

History of original corner establishment:

No record of previous monumentation.

DIAGRAM

T7S R27E
S29
NE-NE-SW
1/256

Description of corner evidence found:

None.

Description of monument and accessories I established to perpetuate the original location of this corner:

At the corner point I set a 2 1/2" X 30" alum. pipe with a 3" alum. cap containing a magnet and marked:

I built a stone mound around the monument.

S29
NE-NE-SW
1/256
PLS 1832
1986

From the corner:

A Ponderosa Pine, 15" dia., S10°W, 64.1 ft.
marked: NE NE SW 1/256 S29 BT

A Ponderosa Pine, 17" dia., N67 1/2°W, 28.5 ft.
marked: X at breast height and BT at base.

BTs have blaze and a 6" stripe painted red, a BT tag, a "Land Survey Monument" sign and an alum. "PLS 1832" washer nailed to the bottom of the blaze. There is a 6' steel fence post with a "Land Survey Monument" sign within 5' of the corner.

Measured to center of BTs using steel tape and staff compass. Magnetic declination set at 18 1/2°E.

April 13, 1986

Office of.....*Surveyor*..... County of.....*Grant*.....
State of.....*Oregon*..... I hereby certify that the within instrument was filed in this office
for record on the.....*25* day of.....*July*....., 19.....*86*
.....*Robert D. Bayliff* by.....
(COUNTY OFFICIAL) (DEPUTY)

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Fayette S. Munro
OREGON
JULY 13, 1979
FAYETTE S. MUNRO
1832