


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Refer to: Plat of Wilson 1985 Cadastral Survey  
Section 29, T.7S., R.27E., W.M.

History of original corner establishment:

No record of previous monumentation.



Description of corner evidence found:

None.

Description of monument and accessories I established to perpetuate the original location of this corner:

At the corner point I set a 2 1/2" X 30" alum. pipe with a 3" alum. cap containing a magnet and marked:

I built a stone mound around the monument.

S29  
C-S-SE  
1/64  
PLS 1832  
1986

From the corner:

A Ponderosa Pine, 13" dia., S52 1/2° E, 178.2 ft. marked: C S SE 1/64 S29 BT

No other tree was available so I drove:

RM, a 5/8" X 30" iron rod (rebar); from the corner S36 1/2° W, 11.7 ft. with 1 1/2" dia. yellow plastic cap marked: PLS 1832.

BTs have blaze and a 6" stripe painted red, a BT tag, a "Land Survey Monument" sign and an alum. "PLS 1832" washer nailed to the bottom of the blaze. There is a 6" steel fence post with a "Land Survey Monument" sign within 5' of the corner and the RM.

Measured to center of BTs using steel tape and staff compass. Magnetic declination set at 18° E.

April 18, 1986

REGISTERED PROFESSIONAL LAND SURVEYOR

Office of... *Surveyor* County of... *Grant*  
State of... *Oregon* I hereby certify that the within instrument was filed in this office  
for record on the... *25* day of... *July* 19... *86*  
*Robert D. Bepko* by... *Fayette S. Munro*  
(COUNTY OFFICIAL) (DEPUTY)

OREGON  
JULY 13, 1979  
FAYETTE S. MUNRO  
1832