


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

C - 21
DIAGRAM

History of original corner establishment:

The original corner was established by Frank W. Campbell on May 10, 1881, under GLO contract No. 380, as follows:

Set a post for 1/4 sec. cor. from which a:
Pine 30" dia. bears W. 11 links. (7.26 feet).
Pine 20" dia. bears N10° E, 27 links (17.82 feet).



Corner evidence recovered:

Found the original bearing tree to the West down and badly decayed. There are no marks remaining on this tree. The root crown of this tree is visible on the east edge of a logging road, and the location of where it stood can be readily determined. The original bearing tree N10° E is lying at the base of the fill slope of the road, having been pushed over during road construction. This tree originally stood where the road was constructed. This tree has full scribing visible and there is also an old bearing tree sign, dated 1955 and marked for "S1", attached to this tree.

Monument and accessories established to perpetuate the original position of this corner:

At a point East, 7.26 feet, from the position of the original 30" bearing tree, as determined by the location of the root crown, I set a 1" x 30" flared, galvanized iron pipe 18" into the ground. A 2 1/2" brass cap attached to the top of the pipe is marked as shown in the diagram above, from which:

- A 10" Ponderosa Pine, scribed "1/4 S1 BT" bears N26° 30' E, 31.6 feet.
- A 15" Ponderosa Pine, scribed "1/4 S1 BT", bears S89° 30' E, 39.1 feet.
- A 18" Ponderosa Pine, scribed "1/4 S2 BT", bears S42° 30' W, 11.1 feet.
- A 14" Ponderosa Pine, scribed "1/4 S2 BT", bears N63° W, 5.9 feet. This tree has an "Oregon State Board of Forestry" location sign attached to the west side, facing the road, which is dated 6 - 30 - 50.

The new bearing trees are scribed on double blazes and have a 3/4" brass washer, marked "PLS 1636", nailed flush to the bottom of the lower blaze.

I hereby certify the above corner was perpetuated as hereon described on July 12, 2001. Magnetic declination set in compass: 18° E.

RECEIVED AND FILED

July 24, 2001

OFFICE OF COUNTY SURVEYOR
Attest: *[Signature]*

[Signature: Dennis L. Gaylord]
REGISTERED PROFESSIONAL LAND SURVEYOR
OREGON
JULY 14 1978
DENNIS L. GAYLORD
1636

Renews June 30, 2003

Recorded at the office of County Surveyor, County of Grant, State of Oregon, on _____, 2001