


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

E - 25  
DIAGRAM



**History of original corner establishment:**

The original corner was established by Henry Meldrum on May 5, 1881, under GLO contract No. 380, as follows:

Set a basalt stone, 16" x 8" x 5", in a mound of stone for cor. to sec's. 1, 6, 7 & 12, from which a:

Pine 24" in dia. bears S48° W, 19 links (12.54 feet).

**Corner evidence recovered:**

Found the corner stone gone, probably rolled down the steep hillside. The original pine bearing tree is now a 24", down Ponderosa Pine with the bark gone. Scribes are visible on previously opened double blazes. The root hole bears S48° W, 12.5 feet.

**Monument and accessories established to perpetuate the original position of this corner:**

At record bearing and distance from the recovered original bearing tree remnants, I set a 1" x 30" flared, galvanized iron pipe 27" into the ground. I build a mound of stones around the pipe. A 2 1/2 brass cap attached to the top of the pipe is marked as shown in the diagram above, from which:

- A 16" Douglas-fir, scribed "T7S R30E S6 BT", bears N54° E, 10.3 feet.
- A 17" Douglas-fir, scribed "T7S R30E S7 BT", bears S51° E, 33.9 feet.
- A 14" Douglas-fir, scribed "T7S R29E S12 BT", bears S61° W, 32.0 feet.
- A 18" Douglas-fir, scribed "T7S R29E S1 BT", bears N85° 30' W, 30.6 feet.

The new bearing trees are scribed on double blazes and have a 3/4" brass washer, marked "PLS 1636", nailed flush to the bottom of the lower blaze.

I hereby certify the above corner point was perpetuated as hereon described on July 26, 2001, Magnetic declination set in compass: 18° E.

Renews June 30, 2003

Recorded at the office of County Surveyor, County of Grant, State of Oregon, on SEPT 18, 2001.

*Robert D. Baggett*  
Co. Surveyor