

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


J - 11
DIAGRAM

History of original corner establishment:

The original corner was established by Frank W. Campbell on May 13, 1881, under GLO contract No. 380, as follows:

Set a post for 1/4 sec. cor. from which a:

Pine 30" dia. bears N39° E, 114 links (75.24 feet).
Pine 24" dia. bears S14° W, 92 links (60.72 feet).



Corner evidence recovered:

A broken and badly decayed 27" Ponderosa Pine stump with visible scribes, "1/4 BT" on double blazes, bears N39° E, 75.24 feet.
A broken and badly decayed 24" Ponderosa Pine stump with visible scribes, "1/4 BT" on double blazes, bears S14° W, 60.72 feet.

Monument and accessories established to perpetuate the original position of this corner:

At record bearing and distance from the original bearing tree remnants, I set a 1" x 30" flared, galvanized iron pipe 16" into the ground to bedrock. I build a mound of stones around the pipe. A 2 1/2" brass cap attached to the top of the pipe is marked as shown in the diagram above, from which:

A 14" Ponderosa Pine, scribed "1/4 S9 BT", bears N37° E, 22.4 feet.
A 13" Ponderosa Pine, scribed "1/4 S16 BT", bears S4° E, 76.0 feet.
A 7" Ponderosa Pine, scribed "1/4 S16 BT", bears S62° W, 49.8 feet.
A 21" Ponderosa Pine, scribed "1/4 S9 BT", bears N 76° W, 63.5 feet.

The new bearing trees are scribed on double blazes and have a 3/4" brass washer, marked "PLS 1636", nailed flush to the bottom of the lower blaze.

I hereby certify the above corner point was perpetuated as hereon described on July 11, 2001. Magnetic declination set in compass: 18° E.

RECEIVED AND
FILED

July 24, 2001

OFFICE OF COUNTY SURVEYOR
Attest: *[Signature]*

REGISTERED
PROFESSIONAL
LAND SURVEYOR
[Signature: Dennis L. Gaylord]
OREGON
JULY 14, 1978
DENNIS L. GAYLORD
1636

Renews June 30, 2003

Recorded at the office of County Surveyor, County of Grant, State of Oregon, on _____, 2001