


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

J - 19
DIAGRAM



History of original corner establishment:

The original corner was established by Frank W. Campbell on May 10, 1881, under GLO contract No. 380, as follows:

Set a post for 1/4 sec. cor., from which a:

- Pine 6" in dia. bears North, 56 links (36.96 feet).
- Pine 6" in dia. bears S30° W, 29 links (19.14 feet).

Corner evidence recovered:

Found the original Ponderosa Pine bearing tree bears north, 36.96 feet. This tree is down and decayed, with scribes, "1/4S BT", visible on double blazes. The root hole where this tree once stood is very obvious. An old location sign on a nearby fir stump indicates this to be the original bearing tree to the north. The original bearing tree to the southwest is gone.

Monument and accessories established to perpetuate the original position of this corner:

At record bearing and distance from the recovered bearing tree remnants, I set a 1" x 30" flared, galvanized iron pipe 26" into the ground. I build a small mound of stones around the pipe. A 2 1/2" brass cap attached to the top of the pipe is marked as shown in the diagram above, from which:

- A 23" Ponderosa Pine, scribed "1/4 S11 BT", bears N50° 30' E, 49.9 feet.
- A 9" Ponderosa Pine, scribed "1/4 S14 BT", bears East, 10.5 feet.
- A 14" Ponderosa Pine, scribed "1/4 S14 BT", bears S77 ° W, 50.0 feet.
- A 19" Ponderosa Pine, scribed "1/4 S11 BT", bears N58° 30' W, 66.8 feet.

The new bearing trees are scribed on double blazes and have a 3/4" brass washer, marked "PLS 1636", nailed flush to the bottom of the lower blaze.

I hereby certify the above corner point was perpetuated as hereon described on July 25, 2001. Magnetic declination set in compass: 18° E.

Dennis L. Gaylord
REGISTERED PROFESSIONAL LAND SURVEYOR
OREGON JULY 14, 1978 DENNIS L. GAYLORD 1636

Renews June 30, 2003

Recorded at the office of County Surveyor, County of Grant, State of Oregon, on SEPT. 18, 2001.

Robert D. Baggett
Co. Surveyor