


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

L - 13  
DIAGRAM

History of original corner establishment:

The original corner was established by Frank W. Campbell on May 12, 1881, under GLO contract No. 380, as follows:

Set a post for 1/4 sec. cor., from which a:  
Pine 12" in dia. bears S81° E, 36 links (23.76 feet).  
Pine 12" in dia. bears N78° W, 18 links (11.88 feet).



Corner evidence recovered:

A 29" sawn and decayed Ponderosa Pine stump with scribe, "T", visible under 6" of overgrowth wood, bears S81 ° E, 23.76 feet.  
A 34" sawn and decayed Ponderosa Pine stump with scribes, "BT", visible under 8" of overgrowth wood, bears N78° W, 11.88 feet.

Monument and accessories established to perpetuate the original position of this corner:

At record bearing and distance from the original bearing tree remnants, I set a 1" x 30" flared, galvanized iron pipe 27" into the ground. A 2 1/2" brass cap attached to the top of the pipe is marked as shown in the diagram above, from which:

- A 22" Ponderosa Pine, scribed "1/4 S15 BT", bears N23° 45' E, 55.9 feet.
- A 13" Ponderosa Pine, scribed "1/4 S15 BT", bears S33° E, 74.8 feet. This tree is in a north-south fence line.
- A 14" Ponderosa Pine, scribed "1/4 S16 BT", bears S46° W, 54.2 feet.
- A 16" Ponderosa Pine, scribed "1/4 S16 BT", bears N26° W, 30.7 feet.

The new bearing trees are scribed on double blazes and have a 3/4" brass washer, marked "PLS 1636", nailed flush to the bottom of the lower blaze.

I hereby certify the above corner point was perpetuated as hereon described on July 9, 2001. Magnetic declination set in compass: 18° E.

RECEIVED AND FILED

July 24, 2001

OFFICE OF COUNTY SURVEYOR  
*Robert P. Bayart*  
Attest: *R. P. Bayart*

REGISTERED PROFESSIONAL LAND SURVEYOR

*Dennis L. Gaylord*

OREGON  
JULY 14 1998  
DENNIS L. GAYLORD  
1636

Renews June 30, 2003

Recorded at the office of County Surveyor, County of Grant, State of Oregon, on \_\_\_\_\_, 2001.