


**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

**History of original corner establishment:** Corner established in 1881 by Henry Meldrum under General Land Office Contract No. 380.

Surveyor General Records (notes) states:

- Set a pine post for Cor to Secs. 5, 6, 31, 32 from which a
- Fir 7 in. in dia. bears N31°E, 50 lks. dist.
- Fir 16 in. in dia. bears N17°W, 21 lks. dist.
- Fir 16 in. dia. bears S67°W, 32 lks. dist.
- Fir 30 in. in dia. bears S45°E, 40 lks. dist.



(No subsequent remonumentations in county records)

**Description of corner evidence found:**

Found a 16 in. fir, live, in good condition, with scribing visible, bearing N31°E, 30.6 ft. from corner position.

Found a 36 in. fir snag with scribing faintly visible bearing S45°E, 26.4 ft. from corner position.

Found a 36 in. fir, live, in good condition, with grown-over blazes bearing S67°W, 21.1 ft. dist. from the corner.

**Description of monument and accessories established to perpetuate the original location of this corner**

Set a 30 in. x 2½ in. iron pipe with 3 in. brass cap marked as shown, 25 in. in the ground for the corner to Secs. 31, 32, 5 & 6, from which new BT's

- A fir 36 in. diam. bears N17°W, 19.4 ft. dist. marked T6S, R31E, S31 BT.
- A fir 9 in. diam. bears S40°E, 44.9 ft. dist. marked T7S, R31E, S5 BT.


Distances taken to a brass washer in the blaze of each tree.

Set a steel fence post approximately 5 ft. West from corner with Attention sign attached.

Used steel tape and magnetic compass with declination = 20°E.

**REGISTERED  
PROFESSIONAL  
LAND SURVEYOR**

*Douglas M. Ferguson*  
**OREGON  
JULY 12, 1908  
DOUGLAS M. FERGUSON  
848**



Office of County Surveyor County of Grant  
Oregon  
 State of Oregon, I hereby certify that the within instrument was filed in this office  
 for record on the 16 day of Nov.; 1972, at 1 o'clock Pm., (signed)  
*Douglas M. Ferguson* by \_\_\_\_\_  
 (COUNTY OFFICIAL) (DEPUTY)

*CORNER UPDATED  
SEE RE-MON SHEET  
FILED JAN 25, '83*