


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established 1881 by Forest W. Campbell under G.L.O.
Contract No. 380. Surveyor General records state:

Top of ridge set Basalt stone 15"x10"x7".



Description of corner evidence found:

Circle of stone 5 ft. in diameter with stone 15"x10"x7" on ridge top.
Accepted as original corner.

Description of monument and accessories established to perpetuate the original location of this corner

St 2 1/2" Brass Cap ON 2 1/2"x30" Gal. steel pipe marked as shown 15" in ground built mound of stone around monument and buried original stone along side of monument.

From which:


- 10" Juniper bears N74°W, 125.4 ft. scribed T7SR31ES11 upper blaze and a lower blaze scribed BT and with a Brass disk stamped PLS 896.
- 14" Juniper bears S76°W, 110.2 ft. scribed T7SR31ES14 upper blaze and a lower blaze scribed BT and with a Brass disk stamped PLS 896.
- 10" Juniper bears N34°E 205.0 ft. scribed T7SR31ES12 upper blaze and a lower blaze scribed BT and with a Brass disk stamped PLS 896.
- 10" Juniper bears S79°E, 30.2 ft. scribed T7SR31ES13 upper blaze and a lower blaze scribed BT and with a Brass disk stamped PLS 896.
- Set guard post with sign 54-4 3 ft. North.
- Posted signs 54-4 and 54-3 on BT's.

Painted red ring around BT's and painted blazes red.

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

Larry D. Bishop

**OREGON
JULY 11, 1989
LARRY D. BISHOP
896**



Office of *Surveyor* County of *Grant*
State of *Oregon*, I hereby certify that the within instrument was filed in this office
for record on the *23* day of *Jan* 1981
Robert D. Bayest by _____
(COUNTY OFFICIAL) (DEPUTY)

Supersedes Sheet filed 12-31-80