


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by Forest W. Campbell under G.L.O. Contract No. 380. Surveyor General records state:  
Set Basalt stone 22"x7"x6" in raised mound of stone.



Description of corner evidence found:

Circle of stone 5 ft in diameter with stone 22"x8"x6" in nearby fence jack-accepted center of circle as original position.

Description of monument and accessories established to perpetuate the original location of this corner

Set 2 1/2" Brass Cap on 2 1/2" x 30" Gal. steel pipe marked as shown 5" in ground built mound of stone around monument.

From which:


10" Juniper bears S19°E, 46.9 ft. scribed 1/4 S13 upper blaze and a lower blaze scribed BT and with a Brass disk stamped PLS 896.

14" Pine bears N63°W, 102.7 ft. scribed 1/4 S14 upper blaze and a lower blaze scribed BT and with a Brass disk stamped PLS 896.

Set steel post with signs 54-4 and 54-2 5 ft. West.

Posted signs 54-4 and 54-3 on BT's.

Painted red band around BT's and painted blazes red.



REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Larry D. Bishop*

OREGON  
JULY 11, 1969  
LARRY D. BISHOP  
896

Office of *Surveyor* County of *Grant*  
State of *Oregon*, I hereby certify that the within instrument was filed in this office  
for record on the *31* day of *Dec* 1980  
*Robert D. Baggett* by \_\_\_\_\_  
(COUNTY OFFICIAL) (DEPUTY)