


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by Forest W. Campbell under G.L.O.
Contract No. 380. Surveyor General records state:
Set Basalt stone 18"x10"x7" in mound of stone.



Description of corner evidence found:


Mound of stone 3 ft. in diameter 18" high center stone 18"x10"x8".

Description of monument and accessories established to perpetuate the original location of this corner

Set 2½" Brass Cap on 2½" x 30" Gal. steel pipe marked as shown 5" in ground, built mound of stone around original stone and monument.

From which:

- 14" Pine bears N75°E, 27.9 ft. scribed ¼S24 upper blaze and a lower blaze scribed BT and with a Brass disk stamped PLS 896.
- 6" Pine bears N62°W, 44.1 ft. scribed ¼S23 upper blaze and a lower blaze scribed BT and with a Brass disk stamped PLS 896.
- Set steel guard post 7 ft. North with sign 54-4.
- Posted signs 54-4 and 54-3 on BT's.
- Painted red band around BT's and painted blazes red.



**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

Larry D. Bishop

**OREGON
JULY 11, 1980
LARRY D. BISHOP
896**

Office of Surveyor County of Gant
 State of Oregon, I hereby certify that the within instrument was filed in this office
 for record on the 31 day of Dec 1980
Robert D. Baggett by _____
 (COUNTY OFFICIAL) (DEPUTY)