


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by Forest W. Campbell under G.L.O. Contract No. 380. Surveyor General records state:

Set Basalt stone 18"x13"x8" and dug pits. From which:  
A 30" Pine bears N32°W, 57 lks.



Description of corner evidence found:

At point established for ¼ corner by compass and hip chain found a stone lying on ground 13"x18"x8". In an area approx. 1½" in diameter which shows fracture as if struck by a chisel there are marks approx. 3/4" high which can be made to read ¼. Fits creek call East. Evidence of remains of Bearing Tree is indistinct at best.

Accepted as original stone.

Description of monument and accessories established to perpetuate the original location of this corner

Set 2½" Brass Cap on 2½"x30" Gal. steel pipe marked as shown 20" in ground, built mound of stone around monument.

From Which:

18" Pine bears N67°W, 4.3 ft. scribed ¼S21 upper blaze and a lower blaze scribed BT and with a Brass disk stamped PLS 896.


12" D-Fir bears S47°W, 30.9 ft., scribed ¼S28 upper blaze and a lower blaze scribed BT and with a Brass disk stamped PLS 896.

Set steel guard post with sign 54-4 3ft. East.

Painted red band around BT's and painted blazes red.

Buried stone along side of monument.

Posted signs 54-3 and 54-4 on BT's.



**REGISTERED  
PROFESSIONAL  
LAND SURVEYOR**

*Larry D. Bishop*

**OREGON  
JULY 11, 1859  
LARRY D. BISHOP  
896**

Office of Surveyor County of Grant  
State of Oregon, I hereby certify that the within instrument was filed in this office  
for record on the 23 day of Jan 1981  
Robert D. Beget by \_\_\_\_\_  
(COUNTY OFFICIAL) (DEPUTY)

*Supersedes Sheet filed 12-31-80*