


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by Forest W. Campbell under G.L.O. Contract No. 380. Surveyor General records state:

Set Basalt stone 19"x10"x10" and dug pits.



Description of corner evidence found:


Circle of stone 4 ft. diameter center stone 18"x11"x10". Accepted as original corner.

Description of monument and accessories established to perpetuate the original location of this corner

Set 2 1/2" Brass Cap on 2 1/2" x 30" Gal. steel pipe marked as shown 18" in ground, buried original stone alongside monument. Built mound of stone around monument.

From which:

- 14" Pine bears N49°E, 184.8 ft. scribed T7SR31ES24 upper blaze and a lower blaze scribed BT and with a Brass Disk stamped PLS 896.
- 14" Pine bears S72°E, 84.3 ft. scribed T7SR31ES25 upper blaze and a lower blaze scribed BT and with a Brass Disk stamped PLS 896.
- 12" Pine bears S28°W, 114.8 ft. scribed T7SR31ES26 upper blaze and a lower blaze scribed BT and with a Brass Disk stamped PLS 896.
- 16" Pine bears N66°W, 111.2 ft. scribed T7SR31ES23 upper blaze and a lower blaze scribed BT and with a Brass Disk stamped PLS 896.



Set steel guard post with signs 54-4 and 54-2 4 ft. South.
Set steel guard post with sign 54-2 5 ft. West.
Posted signs 54-4 and 54-3 on BT's.
Painted red band around BT's and painted blazes red.

REGISTERED PROFESSIONAL LAND SURVEYOR

Larry D. Bishop

OREGON
JULY 11, 1929
LARRY D. BISHOP
836

Office of Surveyor County of Grant
 State of Oregon, I hereby certify that the within instrument was filed in this office
 for record on the 23 day of Jan 1981.
Robert R. Baggett by _____
 (COUNTY OFFICIAL) (DEPUTY)

Supersedes sheet filed 12-31-80