


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: Corner established in 1881 by Meldrum & Campbell under General Land Office Contract No. 380.

Surveyor General records state:

Set a pine post for 1/4 Sec. corner from which a Y. pine 30 ins. diam. bears N67°W, 47 lks. dist.. Y. pine 30 ins. diam. bears N89°E, 97 lks. dist.



Description of corner evidence found:

Found an 18" piece of the original post with scribing visible. Found both BT's. The one to the West is a dead snag stub about 20' tall. The other BT is healthy.

Description of monument and accessories I established to perpetuate the

original location of this corner Set a 2"x30" galvanized pipe with flared end and 2 1/2" brass cap 24" in the ground. Surrounded monument with rock mound 4" high and 24" in diameter. Set two 4"x4"x6' redwood posts 18" in the ground 4' East and North of monument with signs 54-2 & 54-4 on the North post and sign 54-2 on the East post as guard posts for the corner. Scalped bark and painted red band around Bearing Trees and posted signs 54-3 with the following information:

30" Pine Snag	S67°E	31.0'	New BT was scribed	
36" P. Pine	S89°W	65.2'	in upper blaze;	and in lower blaze;
New- 12" P. Pine	S86°E	27.8'	1/4 S26	BT, along with a
				brass nail & washer
				stamped RLS 699

REGISTERED PROFESSIONAL LAND SURVEYOR

Leland Lee Myers

I hereby certify the above corner monument was re-established as herein described on September 27, 1974.


OREGON JULY 9, 1965 LELAND LEE MYERS 699

74846

Office of *County Clerk* County of *Grant*
State of *Oregon*, I hereby certify that the within instrument was filed in this office

for record on the *19* day of *Nov*, 1974 @ *9:59* A.M. Book *1*, Page *208*

John [Signature] (COUNTY OFFICIAL) by *Betty Rowary* (DEPUTY)



INDEXED