

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Index: V-9

Corner Secs. 28, 29, 32 and 33, T.7S., R.31E., W.M.
 Original corner was set by Frank Campbell under
 Contract Number 380 in 1881.

His record reads:

Set a basalt stone 26x15x12 and dug pits for cor. to
 secs. 28, 29, 32, and 33, from which a

Pine 30 ins. in diam. bears S.19°E. 20 lks. dist.

Pine 18 ins. in diam. bears N.29°W. 42 lks. dist.

1	DIAGRAM	1
1	Grant County	1
1	Surveyor	1
1	T7SR31E	1
1	S29 S28	1
1	-----	1
1	S32 S33	1
1	1973	1
1	PLS598	1

In 1973, the Grant County Surveyor remonumented this
 corner. His record reads: Found a basalt stone 16x8x10
 ins. with 1 notch and 4 notches set in a mound of stone, from which
 original bearing trees: A 40" live pine bears S20°E 13.2 ft., marked
 R31E S33 BT in opened blaze. A 22" pine stump, 6' high, bears N29°W,
 28.5 ft. marked T7S S29.

At the corner point: Set a 1 1/2"x36" iron pipe 22" in the ground with
 brass cap marked as shown: from which new bearing trees:

A 14" pine bears N63°E, 48.1 ft. marked T7S R31E S28 BT.

A 12" pine bears S37°W, 43.7 ft. marked T7S R31E S32 BT.

A 14" pine bears N77°W, 66.2 ft. marked T7S R31E S29 BT.

A fence corner of fences running N-S-W bears N45 W., 2 feet.

Description of corner evidence found:

Found the pipe with brass cap stamped as shown in the diagram. From which:

A dead 36" dbh Ponderosa Pine bears S20°E, 13.2' with visible scribe. A

22" dbh Ponderosa Pine stump 6' high bears N29°W, 28.5' with visible

scribe. A 15" dbh Ponderosa Pine stump 4' high bears N63°E, 48.1' with

visible scribe. A 14" dead and down Ponderosa Pine bears S37°W, 43.7'

with visible scribe. A sickly 16" Ponderosa Pine bears N77°W, 66.2' with

healed blaze. Fence corner location is the same except S fence is gone.

Description of monument and accessories I established to perpetuate the

original location of this corner:

The bearings were based on the record bearings of the existing witness
 trees.

I set the following new witness tree:

A 8" dbh Ponderosa Pine bears N63 1/2°E, 18.6' scribed T7SR31ES28BT.

A 9" dbh Ponderosa Pine bears S82°E, 11.6' scribed T7SR31ES33BT.

A 9" dbh Ponderosa Pine bears S22 3/4°W, 22.2' scribed T7SR31ES32BT.

A 9" dbh Ponderosa Pine bears N67 1/4°W, 45.7' scribed T7SR31ES29BT.

An aluminum washer stamped RLS852 is nailed between the letters B and T

on each new tree. All the BT's have LSM and BT signs attached

Painted 6" red bands around all the trees and painted the

scribe blazes red.

This work was completed December 28, 1993.

**REGISTERED
 PROFESSIONAL
 LAND SURVEYOR**

David L. Haddock

**OREGON
 JULY 12, 1968
 DAVID L. HADDOCK
 852**

Office of Surveyor County of Grant
 State of Oregon, I hereby certify that the within instrument was filed
 in this office for record on the 14 day of Feb, 1994.
Robert D. Bayett by _____
 (COUNTY OFFICIAL) (DEPUTY)