

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

---

History of original corner establishment:

Index: V-21

Corner Secs. 25, 26, 35 and 36, T.7S., R.31E., W.M.

Original corner was set by Frank Campbell under Contract Number 380 in 1881.

His record reads:

Set a pine post for corner to sections 25-26-35&36 from which a

Pine 12 ins. diam. bears S10°E, 29 lks. d.

Pine 10 ins. diam. bears N42°W, 60 lks. d.

Pine 30 ins. diam. bears N16°E, 113 lks. d.

Pine 8 ins. diam. bears S48°W, 173 lks. d.

In 1974 OPLS 699 remonumented this corner. His record

reads: Original post was not found. The NW and SE BT's are alive and in fair condition. The NE BT is dead, very rotten and laying down on the

blazed and scribing. Found no evidence of the other BT. Established the corner location using the BT info of above and set 2"x30" galvanized pipe with flared end and 2 1/2" brass cap 26" in the ground. Set a two 4"x4"x6" redwood posts 24" in the ground 4' West and South of the monument. BT information:

24" P. Pine N42°W 40.8'. Dead & down P. Pine N16°E 74.6'. 32" P. Pine S10°E 18.5'. New BT's were scribed in upper blaze:

10" P. Pine N36°E 65.1' T7S R31 S25. 12" P. Pine S74°W 78.8' T7S R31E S35 and BT in lower blaze along with washer stamped RLS 699.

Description of corner evidence found:

Found the galvanized pipe with brass cap stamped as shown in the diagram. From which:

A rotted Ponderosa Pine log bears N16°E, 74.6' with no visible scribe.

A 35" dbh Ponderosa Pine bears S10°E, 18.5' with visible scribe. A 24" dbh 30' high Ponderosa Pine snag bears N42°W, 40.8' with visible scribe.

A 18" dbh Ponderosa Pine bears N36°E, 65.1' with healed blaze.

A 14" dbh Ponderosa Pine bears S74°W, 78.8' with visible scribe.

Description of monument and accessories I established to perpetuate the original location of this corner:

The bearings were based on the record bearings of the existing witness trees.

I set the following new witness tree:

A 16" dbh Ponderosa Pine bears N18 3/4°W, 116.9' scribed T7SR31ES26BT.

An aluminum washer stamped RLS852 is nailed between the letters B and T on the new tree. All the BT's have LSM and BT signs attached.

Painted 6" red bands around all the trees and painted the

scribe blazes red.

This work was completed December 28, 1993.

Office of Surveyor County of Grant

State of Oregon, I hereby certify that the within instrument

in this office for record on the 14 day of Feb

Robert D. Baggs  
( COUNTY OFFICIAL )

by \_\_\_\_\_  
( DEPUTY )

**REGISTERED  
PROFESSIONAL  
LAND SURVEYOR**

*David L. Haddock*  
**OREGON  
JULY 12, 1988  
DAVID L. HADDOCK  
852 94**