


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by Forest W. Campbell under G.L.O.
Contract No. 380. Surveyor General records state:
Set Basalt stone 15"x10"x5" and dug pits.



Description of corner evidence found:


This corner falls on the edge of a rock pit in an area long used as a hunting camp. The original stone no doubt has been moved. No identifiable pits were found.

Description of monument and accessories established to perpetuate the original location of this corner

Set 2½" Brass Cap on 2½" x 30" Gal. steel pipe marked as shown 15" in ground, built a mound of stone around monument.

From which:

- 11" Pine bears S88°W, 19.8 ft. scribed ¼ S32 upper blaze and a lower blaze scribed BT and with a Brass disk stamped PLS 896.
- 15" Pine bears S30°E, 50.9 ft. scribed ¼ S33 upper blaze and a lower blaze scribed BT and with a Brass disk stamped PLS 896.
- Set steel post with signs 54-2 and 54-4 3 ft. South and steel post with sign 54-2 3 ft. East.
- Posted signs 54-3 and 54-4 on BT's.
- Painted red band around BT's and painted blazes red.



**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

Larry D. Bishop

**OREGON
JULY 11, 1980
LARRY D. BISHOP
896**

Office of Surveyor County of Grant
 State of Oregon, I hereby certify that the within instrument was filed in this office
 for record on the 31 day of Dec 1980
Robert D. Bissett by _____
 (COUNTY OFFICIAL) (DEPUTY)