

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Index: X-21

Quarter corner Secs. 35 and 36, T.7S., R.31E., W.M.
 Original corner was set by Frank Campbell under
 Contract Number 380 in 1881.
 His record reads:
 Set a basalt stone 20x12x4 and dug pits for 1/4 Sec.
 corner from which a Y. Pine 40 ins. diam. bears S51°E, 1
 57 lks. d. 1
 In 1974 OPLS 699 remonumented this corner. His record 1
 reads: Found stone of proper size, but could not find 1
 markings. The original BT recently had been burned 1
 down. Could not find any scribing or old metal tags. 1
 By pacing from the section corner to the south and by the notes of Cliff
 Ells of 1968, determined this to be the correct tree and corner location.
 Set a 2"x30" galvanized pipe with flared end and 2 1/2" brass cap 24" in
 the ground. Set a 4"x4"x6" redwood post 20" in the ground 4' North of
 monument. BT information:
 Burned down snag S51°E 37.6'. New BT's were scribed in the upper blazes.
 10" P. Pine S66°E 10.7' 1/4 S36, 10" P. Pine S54°W 22.4' 1/4 S35,
 and BT in lower blaze along with washer stamped RLS 699.

1	DIAGRAM	1
1		1
1	T75R31E	1
1	S351S36	1
1	1/4	1
1	OPLS699	1
1	1974	1
1		1
1		1
1		1

Description of corner evidence found:

Found the galvanized pipe with brass cap stamped as shown in the diagram.
 From which:
 A burned Ponderosa Pine log bears S51°E, 37.6' with no visible scribe.
 A 13" dbh Ponderosa Pine bears S66°E, 10.7' with visible scribe.
 A 12" dbh Ponderosa Pine bears S54°W, 22.4' with visible scribe.

Description of monument and accessories I established to perpetuate the original location of this corner:

The bearings were based on the record bearings of the existing witness trees.
 I set the following new witness trees:
 A 9" dbh Ponderosa Pine bears N47 1/4°E, 28.8' scribed 1/4 S36 BT.
 A 12" dbh Ponderosa Pine bears N25 1/2°W, 24.8' scribed 1/4 S35 BT.
 An aluminum washer stamped RLS852 is nailed between the letters B and T on each new tree. All the BT's have LSM and BT signs attached.
 Painted 6" red bands around all the trees and painted the scribe blazes red.

This work was completed December 28, 1993.

**REGISTERED
 PROFESSIONAL
 LAND SURVEYOR**

David L. Haddock
OREGON
 JULY 12, 1988
DAVID L. HADDOCK
 852

Office of Surveyor County of Grant
 State of Oregon, I hereby certify that the within instrument was filed
 in this office for record on the 14 day of Feb, 1994.
Robert D. Baggett by _____
 (COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

See Maps 1304