


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: Corner established in 1881 by F. W. Campbell under General Land Office Contract No. 380.



Surveyor General Records (Notes) states:
Set a pine post for 1/4 Sec. Cor.
A yellow pine 24 in. bears N49°E 12 lks.
A yellow pine 20 in. bears S34°E 32 lks.

(No subsequent remonumentations in county records)

Description of corner evidence found:

Found a mound of stone from which original BT's
A pine 26 in. dia. bears N49°E 7.9 ft.
A pine 30 in. dia. bears S34E 21.1 ft.

Original post not found.

Description of monument and accessories established to perpetuate the original location of this corner

Set a 30 in. x 2 1/2 in. iron pipe with 3 in. brass cap, marked as shown, 14 in. in ground and erected a mound of stone 3 ft. in diam. around it for the 1/4 Corner between Sections 33 & 4.


From which a new BT
A ponderosa pine 20 in. dia. bears N36°E 17.3 ft. marked T7S R31E 1/4S33 BT.

Distance taken to a brass washer in the blaze of the BT.
Set steel fence post approximately 5 ft. West from corner with Forest Boundary sign attached.

Used steel tape and magnetic compass with declination = 20° E.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Douglas M. Ferguson
OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848



Office of County Surveyor County of Grant
State of Oregon I hereby certify that the within instrument was filed in this office
for record on the 16 day of Nov., 1972, at 1 o'clock p.m., (signed)
Douglas M. Ferguson by
(COUNTY OFFICIAL) (DEPUTY)