


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: Corner established in 1881 by ~~W. Campbell~~ under General Land Office Contract No. 380.

Surveyor General Records (Notes) states:
Set a basalt stone 18x12x4 and raised a mound of stone for corner to Secs. 2, 3, 34 & 35.
A "Y" pine 30 in. bears S69°W 134 lks.



(No subsequent remonumentations in county records)

Description of corner evidence found:

Found 40 in. pine, live in good condition with burned out scribing faintly visible. Bearing S69°W 788.5 ft. from corner position, which falls on fence corner with fences bearing North, South, East & West.

Description of monument and accessories established to perpetuate the original location of this corner

Set a 30 in. x 2 1/2 in. iron pipe with 3 in. brass cap marked as shown set 14 in. in the ground and raised a 3 ft. base and 16 in. high mound of stone around pipe for the corner to Sections 34, 35, 2 & 3.

From which new BT's

- A pine 12 in. diam. bears N51°E 40.1 ft. dist. marked T7S R31E S35 BT.
- A pine 13 in. diam. bears S35°E 80.5 ft. dist. marked T8S R31E S2 BT.
- A pine 16 in. diam. bears N49°W 68.9 ft. dist. marked T7S R31E S34 BT.


Distances taken to the blaze of each tree.

Set a steel fence post approximately 5 ft. South from corner with Forest Boundary sign attached.

Used steel tape and magnetic compass with declination = 20°E.

REGISTERED PROFESSIONAL LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848



Office of County Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 16 day of Nov., 1972, at 1 o'clock Pm., (signed) [Signature] by [Signature] (COUNTY OFFICIAL) (DEPUTY)