


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

E-8

History of original corner establishment: *BLM ESTABLISHED CORNER DURING THE DEPENDENT RESURVEY OF THE SOUTH, EAST, AND WEST BOUNDARIES, A PORTION OF SUBDIVISIONAL LINES, AND SUBDIVISION OF CERTAIN SECTIONS, T.7S., R.32E., WILLAMETTE MERIDIAN, OREGON IN 1968. SET A BRASS TABLET, 3/4" DIAM., 3 1/2" STEM, IN DRILL HOLE IN EXPOSED BEDROCK, WITH TOP MKD.*



From which

*E 1/16 S.5
S.8
1968*

A pine, 10 ins. diam., bears S. 37 E., 22 lks. dist., mkd E 1/16 S 8 BT (1968)

A pine, 12 ins. diam., bears N. 23 W., 40 lks dist., mkd E 1/16 S 5 BT (1968)

Description of corner evidence found: *GLASS CAP, USGLOS, SET IN STONE MKD.*

*E 1/16 S.5
S.8
1968*

From which

A pine, 16" diam., bears N. 27 49' W., 26.00 ft., (RECORD N. 23 W., 40 lks.) WITH HEADED BLAZE AND U.S. FOREST SERVICE 54-3 SIGN ATTACHED

A pine, 14" diam., bears S. 44 13' E., 14.80 ft. (RECORD S. 37 E., 22 lks) WITH HEADED BLAZE AND U.S. FOREST SERVICE SIGN 54-3 ATTACHED.

FALLEN OVER GUARD POST

Description of monument and accessories I established to perpetuate the

original location of this corner: *RESURVEYED BT'S AND ATTACHED U.S. FOREST SERVICE SIGNALS 54-3 AND 54-9. PAINTED 6" RED BAND AROUND BOTH TREES SET NEW STEEL GUARD POST WITH U.S. FOREST SERVICE SIGNALS 54-2 AND 54-9 SIGNALS ATTACHED, 5 FT EAST OF CORNER.*

MAGNETIC DECLINATION USED AT THIS CORNER TO ESTABLISH BEARINGS: *DC; 19° E.*

WITNESS: *KEN BATES
SCOTT KRIKA*

I HEREBY CERTIFY THE ABOVE CORNER POINT WAS PERPETUATED IN OCTOBER 1990, AS HEREON DESCRIBED

REGISTERED PROFESSIONAL LAND SURVEYOR

Guy W. Streamer
OREGON
SEPTEMBER 23, 1977
GUY W. STREAMER, JR.
1341

Office of *Surveyor* County of *Grant*
State of *Oregon*, I hereby certify that the within instrument was filed in this office for record on the *27* day of *Feb*, 19*91*
Robert D. Sargent by _____
(COUNTY OFFICIAL) (DEPUTY)