


**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

E-9

**History of original corner establishment:** THE CORNER OF SECTIONS 4, 5, 8, AND 9 ORIGINALLY MONUMENTED WITH A BASALT STONE, 12 X 8 X 6 ins., FIRMLY SET 5 ins. IN THE GROUND, MKD. WITH 1 NOTCH ON NORTH SIDE AND 3 NOTCHES ON EAST SIDE. BLM SET EXISTING CORNER DURING DEPENDENT RESURVEY, A PORTION OF SUB-DIVISIONAL LINES, AND SUBDIVISION OF CERTAIN SECTIONS, T. 7S., R. 32 E., WILLAMETTE MERIDIAN, OREGON 1968. AT THE CORNER POINT, SET AN IRON POST, 28 ins. LONG, 2 1/2 ins. DIAM., 24 ins. IN THE GROUND, IN A COLLAR OF STONE, WITH BRASS CAP MARKED:



$$\begin{array}{r|l} 55 & 54 \\ \hline 58 & 59 \\ \hline & 1968 \end{array}$$
 (CONT.)

**Description of corner evidence found:** BLM BRASS CAP MKD. T. 7S. R. 32E, SET ON 2 1/2"

$$\begin{array}{r|l} 55 & 54 \\ \hline 58 & 59 \\ \hline & 1968 \end{array}$$

IRON POST IN MOUND OF STONE FROM WHICH

A PINE, 14" DIAM., BEARS N. 29° 20' W., 38.38 FT. (RECORD N. 29 1/2° W., 60 LKS), WITH HEALED BLAZE

A PINE, 18" DIAM., BEARS S. 28° 45' E., 50.99 FT. (RECORD S. 30° 45' E., 70 LKS), WITH HEALED BLAZE

A PINE, 14" DIAM., BEARS S. 85° W., 32.30 FT. DIST., (S. 83 1/4° W., 49 LKS.), HEALED BLAZE

DAMAGED BT (DECAYING TRUNK) A PINE, 15 ins. DIAM., BEARS N. 70° 45' E., 46.0 FT. DIST. (N. 68 1/2° E., 70 LKS), WITH PARTIALLY HEALED BLAZE, ILLEGIBLE SCRIBE MARKS

**Description of monument and accessories I established to perpetuate the**

**original location of this corner:** NEW BEARING TREE, A PINE, 20" DIAM., BEARS N. 18° 30' E., 33.40 FT. DIST, SCRIBED T. 7S., R. 32 E., S 4, BT, BRASS WASHER # 1341, US FOREST SERVICE SIGNS 54-3 AND 54-9 ATTACHED AND 6" RED BAND PAINTED AROUND TREE. THIS BT TO REPLACE DAMAGED TREE.

ATTACHED US FOREST SERVICE SIGNS 54-3 AND 54-9 TO EXISTING B.T.'S!  
PAINTED 6" RED BAND AROUND EXISTING B.T.'S!

SET STEEL GUARD POST 5 FT. WEST OF CORNER WITH US FOREST SERVICE SIGNS 54-2 AND 54-9 ATTACHED

PAINTED DAMAGED TREE AND ATTACHED 54-9 SIGN

MAGNETIC DECLINATION USED AT THIS CORNER TO ESTABLISH BEARINGS: DE; 19° E.

WITNESS: KEN BATES  
MARCIE BATES

I HEREBY CERTIFY THE ABOVE CORNER POINT WAS PERPETUATED IN OCTOBER 1990 AND JANUARY 1991, AS HEREON DESCRIBED.

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Guy W. Streamer, Jr.*

OCT 21 1977  
SEPTEMBER 29, 1977  
GUY W. STREAMER, JR.  
1341

Office of Surveyor County of Grant  
State of OR, I hereby certify that the within instrument was filed in this office  
for record on the 27 day of Feb, 1991  
Robert D. Seft by \_\_\_\_\_  
(COUNTY OFFICIAL) (DEPUTY)