

T7S R32E


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: Index: J-11  
 Quarter corner, Secs. 9 and 16, T.7S., R.32E., W.M.  
 Township originally subdivided by Frank Campbell under  
 Contract No. 380 dated 1881. 1 DIAGRAM 1  
 A retracement survey was made by 1 BLM brass cap 1  
 the BLM under assignment instructions dated 1967. 1 S9 1  
 Their record reads: 1 1/4---- 1  
 40.08 The 1/4 sec. cor. of secs. 9 and 16, determined 1 S16 1  
 from the remains of the original bearing trees: A pine, 1 T7SR32E 1  
 21 ins. diam., bears S. 58° W., 4 lks. dist. with 1 1967 1  
 healed blaze. A root hole, bears N. 50° W., 30 lks. 1 1  
 dist., with a down pine alongside, 14 ins. diam., with 1  
 scribe marks 1/4 S BT visible on open blaze. 1  
 At the corner point  
 Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground,  
 in a mound of stone, 3 ft. base, to top, with brass cap mkd.  
 (see diagram) from which new bearing trees  
 A fir, 11 ins. diam., bears N. 51° E., 38 1/2 lks. dist., mkd. 1/4 S9 BT.  
 (1967) A fir, 14 ins. diam., bears S. 50° E., 61 1/2 lks. dist., mkd.  
 1/4 S16 BT. (1967)


Description of corner evidence found:  
 Found the corner monument as described from which:  
 A dead & down 14" dbh Ponderosa Pine bears N50°W, 19.8' with visible  
 scribe. A 22" dbh Ponderosa Pine bears S58°W, 2.6' with healed blaze.  
 A 14" dbh Douglas Fir bears N51°E, 25.1' with healed blaze.  
 A 20" dbh Douglas Fir bears S50°E, 40.8' with healed blaze.

Description of monument and accessories I established to perpetuate the  
 original location of this corner:  
 Cleared brush and debris from corner and set new bearing trees as  
 follows:  
 A 9" dbh Douglas Fir bears N6°W, 32.4' scribed 1/4 S9 BT.  
 The bearings were based on the record bearings to the existing BT's.  
 An aluminum washer stamped RLS 852 is nailed between the letters B and T  
 on each new tree. All the BT's have LSM and BT signs attached.  
 Painted 6" red bands around all the trees and painted the  
 scribe blazes red.

This work was done July 30, 1993.



David L. Haddock



Office of Surveyor County of GRANT  
 State of OREGON, I hereby certify that the within instrument was filed  
 in this office for record on the 20<sup>th</sup> day of Sept, 1993.  
Robert D. Burgess by \_\_\_\_\_  
 ( COUNTY OFFICIAL ) ( DEPUTY )