


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner originally established by Frank W. Campbell under GLO contract number 468, dated April 12, 1883. Surveyor General record states:

Set a granite stone 16x10x4 ins 11 ins in the ground for ¼ sec cor marked ¼ on N face from which:
 A pine 40 in diam bears N68°W 41 lks dist marked ¼S BT
 A pine 36 in diam bears S36°E 91 lks dist marked ¼S BT
 Corner remonumented in 1977 by Craig L. Wanless, BLM Group no. 350. His notes state; The ¼ cor of secs 5 and 32, on the S boundary of the Tp monumented with the original unmarked granite stone, 16x10x4 ins firmly set 4 ins in the ground in a collar of stones, from which the remains of the original bearing trees; A sawed pine stump, 41 ins diam, bears N68°W 41 lks dist with scribes visible. A pine snag 38 ins diam bears S36°E 91 lks dist with scribes visible. At the corner point set an iron post in a mound of stone 2 ft base to top with brass cap marked; (markings shown below) from which new bearing trees: A pine 10 ins diam bears N14°W 32 lks dist marked ¼ S32 BT. A pine 10 ins diam bears S27°W 47 lks dist marked ¼ S5 BT.
 Deposit corner stone alongside iron post.
 No record of subsequent monumentation found in Umatilla County survey records.



Description of corner evidence found:


Found a standard BLM brass cap marked as shown, in a mound of stone.

Original BTs:

Found an 34 inch diameter pine snag S36°E, 91 lks dist, dead and standing with blaze evident.
 Found a 39 inch diameter Pine stump N68°W, 41 lks dist, rotting with scribes visible.

BLM BTs:

Found a 12 inch diameter Douglas Fir S27°E, 47 lks dist, sick and dying with blaze evident.
 Found a 14 inch diameter Douglas Fir N14°W, 32 lks dist, sick and dying with blaze evident.



NOTE:
 BLM record states taking pine bearing trees.

Description of monument and accessories | established to perpetuate the

original location of this corner: From the existing found BLM brass cap monument:

New BTs:

A 10 inch diameter Ponderosa Pine bears N17°E, 43.68 feet marked ¼ S32 BT
 A 10 inch diameter Ponderosa Pine bears S18°E, 70.84 feet marked ¼ S5 BT

Painted a 6 inch red band around all BTs and attached 54-3 and 54-9 signs.

Set a steel fencepost approximately 5 feet East with 54-2 and 54-9 signs attached.

I hereby certify that the above corner point was perpetuated as hereon described on July 21, 1987.

Witness: Rick Robinson



I used a steel tape and magnetic compass in the establishment of new accessories. I used 17° East magnetic declination and the distances are to a 50d spike driven in the right side of the root crown. I attached a brass washer marked OPLS 644 to the BT blaze.

Office of... Surveyor County of... Grant
 State of... Oregon I hereby certify that the within instrument was filed in this office
 for record on the... 26 day of... Aug 19... 87
Robert D. Baggett by
 (COUNTY OFFICIAL) (DEPUTY)