


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

B-1

History of original corner establishment:

David H. Krumbein, PLS 933, set a 2 1/8" x 30" iron pipe with a brass cap marked as shown below. Pipe was 6" in the ground with a mound of stone to the cap.
From the corner:

- A Pine, 16" dia., N37°W, 11.25 ft.; marked: N1/16 S1 T7S R32E BT
- A Pine, 14" dia., S86°E, 31.70 ft.; marked: N1/16 S6 T7S R33E BT



Description of corner evidence found:

I found a 2 1/8" iron pipe with a 2 1/8" brass cap marked in a mound of stone.

T7S
N1/16
S1 S6
R32E R33E
1978
PLS 933

From the corner:

- A Ponderosa Pine, 17" dia., N37°W, 11.25 ft.; with scribing visible.
- A Ponderosa Pine, 11" dia., dead, S86°E, 31.70 ft.; with scribing visible.

Description of monument and accessories I established to perpetuate the original location of this corner:

To maintain the corner I marked a new BT:
A Ponderosa Pine, 17" dia., S18 1/4°E, 52.0 ft.; marked: N1/16 S6 BT
BTs have blaze and a 6" band painted red, BT tags and "Land Survey Monument" signs. New BT has, additionally, an alum. "PLS 1832" washer nailed to the bottom of the blaze. There is a 6' steel fence post with a "Land Survey Monument" sign within 5' of the corner.
Measured to center of BTs using steel tape and staff compass. Magnetic declination set at 19°E..

August 12, 1989

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Fayette S. Munro

OREGON
JULY 13, 1979
FAYETTE S. MUNRO
1832

RECEIVED AND
FILED

DEC 17 1989

OFFICE OF COUNTY SURVEYOR
Robert D. [Signature]
Attest:

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....
..... by

(COUNTY OFFICIAL)

(DEPUTY)