


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:	Index:	C-5
Quarter cor., Secs. 6 & 5, T.7S., R.33E., W.M.		
Corner originally set by William Gradon under	1	DIAGRAM
Contract No. 579 in 1884.	1	
His record reads: Set a basalt stone 18"x12"x6" 12 in.	1	
in ground marked 1/4 on north face.	1	
A Pine 36" diam. bears S59°E 107 lks. marked 1/4S BT.	1	T7S R33E
A Pine 36" diam. bears N85°W 70 lks. marked 1/4S BT.	1	1/4
In 1978, PLS 933 remonumented this corner. His record	1	S6 S5
reads: Found stone 18"x12"x5 1/2" 5in. in ground.	1	1978
Found 40" pine stump N85°10'W 70 lks. with old sign.	1	PLS933
Found 38" pine down S58°E 107 lks. with old sign.	1	
Set 2 1/2"x30" iron pipe 22" in ground with brass cap		
marked as shown from which I scribed two new bearing trees: Pine 12 in.		
dia. bears N28°23'W 43.40 ft. marked 1/4 S6 BT. Pine 11 in. dia. bears		
N65°49'E 17.01 ft. marked 1/4 S5 BT.		
In 1991 PLS 1341 found all the accessories set by PLS 933. He added the		
following BT: A pine, 19" diam., bears N01°30'W., 28.20 ft dist. scribed		
1/4 S6 BT.		

Description of corner evidence found:
 Found the corner monument as described from which:
 A 17" dbh Ponderosa Pine bears N33 1/2°W, 43.4' with healed blaze.
 A 11" dbh Ponderosa Pine bears N65 1/4°E, 17.0' with visible scribe.
 A 19" dbh Ponderosa Pine bears N88°W, 28.2' with visible scribe.
 A dead and down 38" dbh Ponderosa Pine bears S58°E, 70.0' with healed blaze. A 40" Ponderosa Pine stump bears N85°W, 46.2' with no visible marks.

Description of monument and accessories I established to perpetuate the original location of this corner:
 Cleared brush and debris from corner and set new bearing tree as follows:
 A 9" dbh Ponderosa Pine bears S25 1/2°E, 24.2' scribed 1/4 S5 BT.
 The bearings are true based on the GPS bearings to the surveyed steel post which bears N88 1/2°W, 50.6'.
 An aluminum washer stamped RLS 852 is nailed between the letters B and T. on the new tree. All the BT's have LSM and BT signs attached.
 Painted 6" red bands around all the trees and painted the scribe blazes red.

This work was done May 25, 1994.



David L. Haddock



Office of *Surveyor* County of *Grant*
 State of *Oregon*, I hereby certify that the within instrument was filed
 in this office for record on the *26* day of *July*, 19*94*.
Robert D. Baggett by _____
 (COUNTY OFFICIAL) (DEPUTY)