CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner not previously established.

DIAGRAM

T7S R35½E
C-S-S-SE
1/256 S34
1983
PLS848

Description of corner evidence found:

N/A

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30"x2½ aluminum pipe with a 2½" aluminum cap stamped as shown in diagram.
Set 2?" in the ground.
From which:
A Fir 12" dia. bears S45°E, 5.4 ft. scribed C-S-S-SE 1/256 S34 BT.
A Fir 11" " " N10°W, 15.0 ft. " " " " " "
Set steel posts with warning and boundry signs, North 5 ft. and West 5 ft.
Nailed brass washers stamped PLS848, bearing tree and warning signs to each tree.
Painted 6" red band around each tree.

REGISTERED PROFESSIONAL LAND SURVEYOR
OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Corner monumented 8-31-83
Witnessed by Dan Martin

Office of Surveyor *County of* Grant
State of Oregon, *I hereby certify that the within instrument was filed in this office for record on the* 22 *day of* Nov, *19* 83
Robert D. Bazett *by* .....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆GPO—798-276

Y 3/4 - 16