


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

This corner was originally established by Deputy Aaron F. York in 1878 under contract #309. Set stone 18"x10"x8". Raised mound of stone at corner.



Description of corner evidence found:

Stone 17"x10"x8" (record above) with faint illegible chisel marks on West, tipped over on West side.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2 1/2"x30" alum. pipe with a 2 1/2" alum. cap 4" in ground in a mound of stone and earth 4 1/2" base to top. Stamped: Buried original stone South and adjacent to monument.

T8S R27E
1/4
S20|S21
1992
LS 896

Marked:

8" Juniper--N53 3/4W 86.2' Scribed 1/4 S20 BT.
14" Juniper--N74 1/2W 51.8' Scribed 1/4 S20 BT.
12" Juniper--S32 1/2W 99.3' Scribed 1/4 S20 BT.
18" Juniper--S62 3/4E 47.6' Scribed 1/4 S21 BT.
Nailed 54-9 and 54-3 signs to BT's, painted bands and blazes red and nailed a 1" brass disk stamped PLS 896 flush between the B and the T, Set guard post SE with 54-9 sign.
Dec. 20.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Larry D. Bishop

OREGON
JULY 11, 1993
LARRY D. BISHOP
008

Office of Surveyor County of Grant
State of Ore. gov, I hereby certify that the within instrument was filed in this office
for record on the 20 day of Jan, 1993
Robert D. Baggett by Grant
(COUNTY OFFICIAL) (DEPUTY)