


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

T.8S., R.31E., INDEX L-20

History of original corner establishment:

This corner was originally established by Douglas Ferguson as shown on Grant County Map of Survey No 599.



Description of corner evidence found:

Found a Brass capped monument and accessories as shown on Map of Survey No. 599. Due to the correction of certain corners as shown on Grant County Map of Survey No. 1707, the position of this corner is amended and a new monument is set.

Description of monument and accessories I establish to perpetuate the original location of this corner:

At the position determined by survey(See Map of Survey No. 1707), set a 2-1/2" x 30" aluminum pipe monument w/3" dia. cap stamped as shown in the DIAGRAM, 18" in the ground, raised a 3' dia. x 1' high mound of earth and stone, from which:

A Juniper, 12" dia. bears N28°00'W, 37.8 ft., scribed C-E 1/16 S14 BT
Original BT's destroyed by logging.

The brass capped monument from Map of Survey 599 bears S84°54'33"W, 30.43 ft.,
Stamped "RM, 30.4" with arrow pointing toward new cap.

Painted red bands around BT's and painted blaze faces.
Placed Land Survey Monument signs and Bearing Tree tags on each BT.
Attached a Brass washer stamped "PLS 848" to the blaze face
of the new BT's.

DIAGRAM

T8S R31E
E 1/16
C-+-C
S14
2003
PLS 848

Measurements to accessories taken with a magnetic compass, declination 20° East, and distances measured with nylon clad steel tape.

I hereby certify that the above corner point was perpetuated as shown hereon on June 4, 2003

Witness: D. Mitchell Ferguson, LSIT
David Herburger, Field Tech.

Office of County Surveyor _____ County of Grant
State of Oregon. I hereby certify that the within instrument was filed in this office
for record on the 10 day of Aug, 2004
Douglas M. Ferguson by _____
County Surveyor Deputy

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

RENEWAL DATE:
01/01/2006