


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: Corner established in 1881 by F. W. Campbell under General Land Office Contract No. 380.

Surveyor General Records (Notes) states:
Set a basalt stone 18x10x5 and dug pit for 1/4 section corner.



(No subsequent remonumentations in county records)

Description of corner evidence found:

Found basalt stone 18x10x5 in. with 1/4 marked faintly on face, surrounded by a mound of stone.

Found original blaze line running East.

Found old blaze line running South.

Accepted stone as corner position.

Description of monument and accessories established to perpetuate the original location of this corner

Set 30 in. x 2 1/2 in. iron pipe with brass cap marked as shown, set 10 in. in the ground. Placed original stone North and alongside pipe and raised a 4 ft. diam. x 2 ft. mound of stone around pipe for 1/4 Corner between Sections 14 & 23.

From which new BT's

A pine 14 in. diam. bears S62°E 14.4 ft. dist. marked T8S R31E 1/4S 23 BT.

A pine 16 in. diam. bears N15°W 52.7 ft. dist. marked T8S R31E 1/4S 14 BT.


Distance taken to a brass washer in the blaze of each tree.

Set a steel fence post approximately 5 ft. West from corner with Forest Boundary sign attached.

Used steel tape and magnetic compass with declination = 20°E.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Douglas M. Ferguson
OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848



Office of...County Surveyor... County of...Grant...
State of...Oregon... I hereby certify that the within instrument was filed in this office
for record on the 16 day of Nov., 1972, at 1 o'clock Pm., (signed)
Douglas M. Ferguson by _____
(COUNTY OFFICIAL) (DEPUTY)