


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

T.8S., R.31E., INDEX P-15

History of original corner establishment:

This corner not previously established.



Description of corner evidence found:

Description of monument and accessories I establish to perpetuate the original location of this corner:

At the position determined by survey (See Map of Survey No. 1707), set a 2-1/2" x 30" aluminum pipe monument w/3" dia. cap stamped as shown in the DIAGRAM, 27" in the ground, from which:

- A Juniper, 10" dia., bears N58°45'W, 39.0 ft., scribed C1/4 S22 BT.
- A Ponderosa Pine, 12" dia., bears N12°30'E, 37.2 ft., scribed C1/4 S22 BT.
- A Ponderosa Pine, 10" dia., bears S18°30'E, 26.8 ft., scribed C1/4 S22 BT.
- A Ponderosa Pine, 10" dia., bears S50°15'W, 29.0 ft., scribed C1/4 S22 BT.

DIAGRAM

Painted red bands around BT's and painted blaze faces.
 Placed Land Survey Monument signs and Bearing Tree tags on each BT.
 Attached a Brass washer stamped "PLS 848" to the blaze face
 of the new BT's.

T8S R31E
 C1/4
 -
 S22
 2003
 PLS 848

Measurements to accessories taken with a Leica TCA 1100 total station.

I hereby certify that the above corner point was perpetuated as shown hereon on April 4, 2003

Witness: D. Mitchell Ferguson, LSIT
Brad Cates, LSIT

REGISTERED
 PROFESSIONAL
 LAND SURVEYOR

OREGON
 JULY 12, 1968
 DOUGLAS M. FERGUSON
 848

RENEWAL DATE:
 01/01/2006

Office of County Surveyor County of Grant
 State of Oregon. I hereby certify that the within instrument was filed in this office
 for record on the 12 day of Aug, 2003

Robert D. Baynet by _____
 County Surveyor Deputy