


**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

T.8S., R.31E., INDEX P-16

**History of original corner establishment:**

This corner not previously established.



**Description of corner evidence found:**

**Description of monument and accessories I establish to perpetuate the original location of this corner:**

At the position determined by survey (See Map of Survey No. 1707), set a 2-1/2" x 30" aluminum pipe monument w/3" dia. cap stamped as shown in the DIAGRAM, 27" in the ground, from which:

- A Juniper, 12" dia. bears N20°30'W, 117.5 ft., scribed CE1/16 S22 BT
- A Juniper, 16" dia. bears N42°45'E, 125.4 ft., scribed CE1/16 S22 BT

**DIAGRAM**

Painted red bands around BT's and painted blaze faces.  
 Placed Land Survey Monument signs and Bearing Tree tags on each BT.  
 Attached a Brass washer stamped "PLS 848" to the blaze face  
 of the new BT's.

T8S R31E  
 CE 1/16  
 S22  
 2003  
 PLS 848

Measurements to accessories taken with a magnetic compass, declination 20° East, and distances measured with nylon clad steel tape.

I hereby certify that the above corner point was perpetuated as shown hereon on May 29, 2003

Witness: D. Mitchell Ferguson, LSIT  
 David Herburger, Field Tech.

REGISTERED  
 PROFESSIONAL  
 LAND SURVEYOR

*[Signature]*  
 OREGON  
 JULY 12, 1988  
 DOUGLAS M. FERGUSON  
 848

Office of County Surveyor County of Grant  
 State of Oregon. I hereby certify that the within instrument was filed in this office  
 for record on the 10 day of Aug, 2004

*[Signature]* by \_\_\_\_\_  
 County Surveyor Deputy

RENEWAL DATE:  
 01/01/2006