

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


P-17

**History of original corner establishment:**

Corner originally established by F. W. Campbell under Contract No. 380 dated March 19, 1881. Notes state: Set a basalt stone 20 x 12 x 12 with pits for 1/4 sec. cor.

Corner was re-established by William R. Wells, Grant County Map of Survey No. 599. Record states: At the corner position a 2" x 30" iron pipe with brass cap was set 12" in the ground and surrounded with a mound of stones to cap.

Established 2 new BT's: A 11" Pine bears N69 1/2°E, 7.1 feet scribed 1/4S 23 BT. A 10" Pine bears N49°W 47.4 feet scribed 1/4S 22 BT.



**Description of corner evidence found:**

Found 2 1/2" galvanized iron pipe with 3" brass cap projecting 8" from stone mound. This monument, re-established for the corner on Map of Survey No. 599 in 1979, was rejected due to new evidence found.

REGISTERED PROFESSIONAL LAND SURVEYOR
---

*Will. R. Wells*

OREGON JULY 22, 1977 WILLIAM R. WELLS 1106
---

*renews 6-30-06*

**Description of monument and accessories I established to perpetuate the original location of this corner:**

I establish the corner point by survey and set a 2 1/2" by 30" aluminum pipe with 3 1/4" aluminum cap, marked as shown in Diagram, 24" in the ground and surrounded with a mound of earth and stone. Set steel fence post North of corner and attached sign 54-9. I change the rejected 1979 monument to a reference monument. The reference monument is marked: "RM, T8S R31E, 52.1 FT, 2003, PLS 1106". The reference monument bears South 71°22' West, 52.1 feet from the new corner monument. There is a steel fence post North of reference monument with "Attention" sign attached.

From the new corner point:

A 16" Ponderosa pine with partially healed double blaze bears S76°W, 45.2 feet. (1979 BT), blaze faces SW.

A 14" Ponderosa pine with partially healed double blaze bears N 76 1/2° W, 86.9 feet. (1979 BT), blaze faces SE.

A 12" juniper bears N 22 1/2° W, 33.5' scribed "1/4 S22 BT". (New BT).

A 17" juniper scribed bears N 49° E, 73.2' scribed "1/4 S22 BT". (New BT).

A 5" juniper bears S 65° E, 81.2', scribed "X" at breast height and "BT" at base of tree. (New BT).

New bearing trees have a 3/4" brass washer stamped PLS 1106 nailed to face of blaze. Attached sign 54-3 and 54-9 to all bearing trees.

A East-West wire fence is 45 feet South of the new corner point.

This corner was monumented on May 21, 2003. Used magnetic compass with 18° East declination and measured to accessories with steel tape. Measurements to bearing trees are to the center of tree.

Witness: Jason Wells, LSIT

Office of.....SURVEYOR.....County of.....GRANT.....

State of OREGON, I hereby certify that the within instrument was filed in this office for record on the 12 day of AUG., 2004

.....Robert D. Bryant.....by.....Robert D. Bryant.....

(COUNTY OFFICIAL)

(DEPUTY)