


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

T.8S., R.31E., INDEX P-18

History of original corner establishment:

This corner not previously established.



Description of corner evidence found:

Description of monument and accessories I establish to perpetuate the original location of this corner:

At the position determined by survey (See Map of Survey No. 1707), set a 2-1/2" x 30" aluminum pipe monument w/3" dia. cap stamped as shown in the DIAGRAM, 8" in the ground, raised a 3' dia. x 2' high mound of earth and stone, from which:

A Juniper, 12" dia. bears N23°15'E, 39.9 ft., scribed C-W1/16 S23 BT

A Juniper, 8" dia. bears S71°00'W, 41.5 ft., scribed C-W1/16 S23 BT

DIAGRAM

Painted red bands around BT's and painted blaze faces.
Placed Land Survey Monument signs and Bearing Tree tags on each BT.
Attached a Brass washer stamped "PLS 848" to the blaze face of the new BT's.

T8S R31E
CW 1/16
S23
2003
PLS 848

Measurements to accessories taken with a magnetic compass, declination 20° East, and distances measured with nylon clad steel tape.

I hereby certify that the above corner point was perpetuated as shown hereon on May 8, 2003

Witness: D. Mitchell Ferguson, LSIT
Brad Cates, LSIT

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1988
DOUGLAS M. FERGUSON
848

RENEWAL DATE:
01/01/2006

Office of County Surveyor _____ County of Grant
State of Oregon. I hereby certify that the within instrument was filed in this office
for record on the 10 day of Aug, 2003

Robert D. Smith by _____
County Surveyor Deputy