


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

T.8S., R.31E., INDEX R-9

History of original corner establishment:

This corner was originally established by F. W. Campbell under G.L.O. contract number 380, dated March 19, 1881. Survey General notes state:

NEED ORIGINAL NOTES FOR THIS CORNER



Description of corner evidence found:

Found a 15"x8"x6" stone with 4 grooves on one face and 2 on another, in an old rock jack at a south and east fence corner. Accepted the position of the stone in the rock jack. (See Map of Survey No. 1707)

Description of monument and accessories I establish to perpetuate the original location of this corner:

At the position of the above said fence corner, Set a 2-1/2" x 30" aluminum pipe monument w/3" dia. cap stamped as shown in the DIAGRAM, 22" in the ground, from which;

Set 5/8"x30" rebar pins w/yellow plastic caps marked "FS&E SURVEY MARKER" as follows:

- N45°00"W, 16.3 ft., no mark on top of pin
- N45°00"E, 19.1 ft., filed 1 groove on top of pin
- S45°00"E, 13.4 ft., filed 2 grooves on top of pin
- S45°00"W, 14.6 ft., filed an X on top of pin

DIAGRAM

T8S R31E
 S20 | S21

 S29 | S28
 2003
 PLS 848

Measurements to accessories taken with a magnetic compass, declination 20° East, and distances measured with nylon clad steel tape.

I hereby certify that the above corner point was perpetuated as shown hereon on May 6, 2003

Witness: D. Mitchell Ferguson, LSIT
Brad Cates, LSIT

REGISTERED
 PROFESSIONAL
 LAND SURVEYOR

OREGON
 JULY 12, 1968
 DOUGLAS M. FERGUSON
 848

RENEWAL DATE:
 01/01/2006

Office of County Surveyor _____ County of Grant
 State of Oregon. I hereby certify that the within instrument was filed in this office
 for record on the 12 day of Aug, 2003

Robert D. Leggett by _____