

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established by W. B. Barr, Deputy Surveyor General, during the original survey Contract No. 492 dated April, 1884.

Set Fir Post 4 ft long 4 ins square 24 ins in the ground for cor to secs 21, 22, 27 and 28 marked T8S S22 on NE, R35 1/2 E S27 on SE, S28 on SW and S21 on NW faces with 3 notches on E and 2 notches on S edges from which

- A Pine 48 ins. diam. bears N80°E, (30.4')46 lks. blazed and scribed T8SR35 1/2 E S22 BT
- A Fir 24 ins. diam. bears S70°E, (63.4')96 lks. blazed and scribed T8SR35 1/2 E S27 BT
- A Pine 48 ins. diam. bears S10°W, (9.2')14 lks. blazed and scribed T8SR35 1/2 E S28 BT
- A Pine 18 ins. diam. bears N40°W, (62.7')95 lks. blazed and scribed T8SR35 1/2 E S21 BT

DIAGRAM

T8S R35 1/2 E

S21	S22
S28	S27

1983
RLS 699

Description of corner evidence found:

Found no evidence of the original post.

- 48" Ponderosa pine (18" Stump)(No Visible Marks)(1884 BT) bears N78°E, 30.4 feet.
- 24" Douglas-fir (18" Stump)(Scribing Visible)(1884 BT) bears S78° 15'E, 63.4 feet.
- 48" Ponderosa pine (18" Stump)(No Visible Marks)(1884 BT) bears S18° 30'W, 9.2 feet.
- 18" Ponderosa pine (Dead & Down)(Scribing Visible)(1884 BT) bears N37° 45'W, 62.7 feet.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 3 1/4" aluminum cap, marked as shown in the diagram, 24" in the ground, at the point determined by the bearing trees. Built a mound of earth & rock to be 30" in diameter by 6" high around the monument, from which new BTs are:

- 13" Douglas-fir bears S39° 45'W, 30.8 feet scribed T8SR35 1/2 E S28 BT
- 8" Ponderosa pine bears N60° 15'W, 10.1 feet scribed T8SR35 1/2 E S21 BT
- 9" Douglas-fir bears N59° 45'E, 34.7 feet scribed T8SR35 1/2 E S22 BT
- 16" Ponderosa pine bears S59° 30'E, 46.8 feet scribed T8SR35 1/2 E S27 BT

Attached BT and Attention signs to and painted a red band around each BT. Bearings were taken with a staff compass, using a declination of 18° 30'E, to the scribed blazes which were painted red. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground. Set a steel fence post 5 feet S of the corner with an Attention sign attached. The monument is not a National Forest property corner.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on November 21, 1983, I monumented the corner as herein described.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Leland L. Myers

OREGON
JULY 9, 1965
LELAND LEE MYERS
699

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 16 DAY OF OCT, 1985

Robert O. Bayliff, Co. Sur.

no 7125