

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


History of original corner establishment:

Corner established by W. B. Barr under G.L.O. contract number 492 dated August 22, 1883.

Set a pine post 4 ft. long 3 ins. square 2 1/4 ins. in the ground marked 1/4 S on N. face for 1/4 sec. cor. from which:

A pine 36 ins. diam. bears S. 35° W., 60 lks. dist. marked 1/4 S BT

A pine 12 ins. diam. bears N. 20° W., 32 lks. dist. marked 1/4 S BT



Description of corner evidence found:

A 26 in. pine with partial scribing (4 S BT) on partially healed blaze bears S. 35° W., 39.6 ft. dist. (60 lks)

No trace of sec. 22 BT or corner post found.

Description of monument and accessories I established to perpetuate the original location of this corner.

Set a 2 1/2 in. brass cap on a 1 in. iron post 6 ins. above the ground in earth and rock mound marked:

T 8 S R 35 1/2 E

<u>1</u>	<u>S 22</u>
4	S 27


R P E 2 8 0 8
1977

New Bearing Tree:

A fir 20 ins. diam. bears N. 63° E., 55.5 ft. dist. marked 1/4 S 22 BT.

Corner monumented April 17, 1977

Office of.....County Surveyor..... County of.....Grant.....
 State of.....Oregon....., I hereby certify that the within instrument was filed in this office
 for record on the 28 day of Feb., 1978.
Robert D. Baggett by
 (COUNTY OFFICIAL) (DEPUTY)



R-15