


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established by W. B. Barr under G.L.O. contract No. 492, dated August 22, 1883.



He set a pine post 4 ft. long 4 ins. square, 24 ins. in the ground for corner to Secs. 22, 23, 26 and 27, marked T 8 S S 23 on NE, R 35½ E S 26 on SE, S 27 on SW, S 22 on NW with 2 notches on E and S edges from which:

- A pine 12 in. diam. bears N 60° E., 32 lks. dist., mkd. T 8 S R 35½ E S 23 BT
- A pine 6 in. diam. bears S 25° E., 42 lks. dist. mkd. T 8 S R 35½ E S 26 BT
- A pine 12 in. diam. bears S 60° W., 52 lks. dist. mkd. T 8 S R 35½ E S 27 BT
- A pine 12 in. diam. bears N 50° W., 54 lks. dist. mkd. T 8 S R 35½ E S 22 BT

Description of corner evidence found:


Found a 12 in. dead tree with partial standing stump with visible but not legible scribe marks N. 50° W., 35.6 ft. (54 lks.).

Found a 10 in. fallen tree marked T 8 S R 35½ E S 27 BT at edge of logging skid trail S 60° W., 52 lks. dist.

No other BTs or corner post found.

Description of monument and accessories established to perpetuate the original location of this corner

Set a 2½ in. brass cap on a 1 in. iron pipe 10 ins. above ground in earth and rock mound marked:



From which new bearing trees:

- A fir 11 in. diam. bears N 38° E., 33.4 ft. dist., mkd. T 8 S R 35½ E S 23 BT
- A fir 14 in. diam. bears S 67° 15' E., 36.2 ft. mkd. T 8 S R 35½ E S 26 BT
- A larch 11 in. diam. bears S 27° 15' W., 20.9 ft. mkd. T 8 S R 35½ E S 27 BT
- A fir 7 in. diam. bears N 26° 30' W., 32.5 ft. mkd. T 8 S R 35½ E S 22 BT

Corner reestablished Jan. 19, 1977.

Office of County Surveyor County of Grant
 State of Ore., I hereby certify that the within instrument was filed in this office
 for record on the 28 day of Feb. 1978
Robert D. Bagat by _____
(COUNTY OFFICIAL) (DEPUTY)

