

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


History of original corner establishment:

Corner originally established by Eugene P. McCormack under GLO contract number 398, dated July 2, 1881. Surveyor General record states:

Set a basalt stone 20x10x8 ins 15 ins in the ground for ¼ sec cor, marked ¼ on W face, from which:

- A Pine 48 ins diam bears East, 73 lks dist marked ¼S BT
- A Pine 10 ins diam bears N55°W, 9 lks dist marked ¼S BT

Corner was remonumented in September, 1979 by William L. Hanley. His notes state: Found a sawed pine stump 46 ins diam for section 28 BT. (no visible scribes). At record location as determined by the bearing tree stump, found a broken basalt stone (now 13x8x6 ins) marked ¼. Set a 2½" brass cap on a 2" iron pipe 31" long 28" in the ground with a surrounding rock mound. Brass cap marked (markings shown below). New bearing trees:
 A pine 10 ins diam bears S82°E, 20.5 ft dist marked ¼ S28 BT
 A pine 8 ins diam bears S22°E, 28.0 ft dist marked X BT




No record of subsequent monumentation found in Grant County survey records.

Description of corner evidence found:

Found a 2 inch brass cap on a 1 inch galvanized iron pipe. Brass cap marked as shown:

Hanley Bearing Trees:
 Found a 11" diameter Ponderosa Pine S82°E, 20.5 feet, Live and vigorous with scribes visible.
 Found a 10" diameter Ponderosa Pine S22°E, 28.0 feet, Live and vigorous with scribes visible.

Original Bearing Tree:
 Found a 48" diameter Ponderosa Pine stump, East, 73 lks, no evidence of blaze visible.



See map of survey dated September, 1987. *No. 1019*
 Description of monument and accessories I established to perpetuate the original location of this corner:

I painted a 6 inch red band around all bearing trees and attached 54-3 and 54-9 signs.

I hereby certify that the above corner point was perpetuated as hereon described on August 9, 1987.

REGISTERED PROFESSIONAL LAND SURVEYOR

[Signature]
 OREGON
 JULY 10, 1964
DUANE I. GRIFFITH
 644

I used a steel tape and magnetic compass in the location of existing accessories. I used 17° East magnetic declination.

Office of *Sumner* County of *Grant*
 State of *Oregon*, I hereby certify that the within instrument was filed in this office for record on the *22* day of *Oct*, 19*87*
Roland D. Baggett by *[Signature]*
 (COUNTY OFFICIAL) (DEPUTY)