CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Refer to Plat of Little Tam 1989 Cadastral Survey
Sections 2 and 11, T.8S., R.25E., W.M.

J-25

DIAGRAM

T8S
R25E | R26E
S12 | S7
S13 | S18

History of original corner establishment:

Alonzo Gesner under G.L.O. contract number 266, dated June 20, 1877, set a stone 20"x 12"x 7" and raised a mound of stone at the corner.

Description of corner evidence found:

I found a stone 16"x 10"x 6" with 4 grooves on one face in a mound of stone.

Description of monument and accessories I established to perpetuate the original location of this corner:

In place of the original stone I set a 2½"x 30" alum. pipe with a 2½" alum. cap containing a magnet and marked: Monument is 14" in ground with original stone buried alongside and surrounded by a mound of stone.

T8S
R25E | R26E
S12 | S7
S13 | S18
PLS 1832
1989

From the corner:

A Ponderosa Pine, 15" dia., N41½°E, 22.9 ft.; marked: T8S R26E S7 BT
A Ponderosa Pine, 20" dia., S3°E, 55.5 ft.; marked: T8S R26E S18 BT
A Ponderosa Pine, 13" dia., S34°W, 22.8 ft.; marked: T8S R25E S13 BT
A Juniper, 10" dia., N68°W, 15.5 ft.; marked: T8S R25E S12 BT

BTs have blaze and a 6" band painted red, BT tags, "Land Survey Monument" signs and alum. "PLS 1832" washers nailed to the bottom of the blaze. There is a 6' steel fence post with a "Land Survey Monument" sign within 5' of the corner.

Measured to center of BTs using steel tape and staff compass. Magnetic declination set at 18°E.

July 8, 1989

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Fayette S. Munro

OREGON
JULY 13, 1979
FAYETTE S. MUNRO
1832

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office for reeprd on the 8 day of Aug, 19 89
Robert D. Bazett by
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

GPO—798-276

J-1