

**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**


R-17

**History of original corner establishment:** This corner originally established by Alonzo Gesner under G.L.O. Contract No. 266 in 1877 as follows:  
Set stone 14"x10"x8" for corner and raised a mound of stones along side.

This corner was perpetuated by Duane I. Griffith PLS 644 on June 9, 1984 as follows:

Replaced marked stone with standard aluminum monument from which: an unrecorded B.T., a 28" ponderosa pine bears north-westerly about 20 feet with a burned face.

- A 9" red fir bears N.31°E., 58.6 feet, scribed "T.8S., R.26E., S23B.T."
- A 14" ponderosa pine bears S.88°E., 36.9 feet, scribed "T.8S., R.26E., S26B.T."
- A 13" ponderosa pine bears S.15°W., 48.0 feet, scribed "T.8S., R.26E., S27B.T."
- A 12" ponderosa pine bears N.83°W., 56.0 feet, scribed "T.8S., R.26E., S22B.T."




**Description of corner evidence found:** A 2½" capped aluminum pipe protruding 3" above a mound of stones which is 3 foot at the base by 18" high. Cap is marked:  
From which bears:

A sawn 15" ponderosa pine stump in the east edge of new road No. 4208020, N.32°W., 17.8 feet, (original unrecorded bearing tree)

- A 9" Douglas-fir, N.34°E., 58.6 feet, scribed as above.
- A 14" ponderosa pine, S.86°E., 36.9 feet, scribed as above.
- A 14" ponderosa pine, S.16°W., 47.7 feet, scribed as above.
- A 12" ponderosa pine, N.80°W., 54.0 feet, scribed as above.

A 6' metal fence post with 54-4 sign attached, west 5.0 feet.

Each of the 4 bearing trees established by Griffith are blazed with double blazes and have a 3/4" brass washer marked "OPLS 644" nailed to the face of the lower blaze, and 54-3 and 54-4 signs nailed to them.



**Description of monument and accessories I established to perpetuate the**

**original location of this corner:** The 14" pine established by Griffith in Section 27 is in danger of being destroyed by further road construction activities. I, therefore, established a new bearing tree:

A 20" ponderosa pine bears S.36°30'W., 126.9 feet, scribed "T.8S., R.26E., S27B.T." on a single blaze. I nailed a 3/4" washer, marked "PLS 1636" to the scribed face in the "B." I nailed 54-3 and 54-4 signs to the tree.

I hereby certify the above corner position was perpetuated as hereon described on July 15, 1986. De: 20°E.

Witness: Steve Scritchfield

**REGISTERED  
PROFESSIONAL  
LAND SURVEYOR**

*Dennis L. Gaylord*

**OREGON**  
JULY 14, 1978  
**DENNIS L. GAYLORD**  
1636

Office of..... County Surveyor..... County of..... Grant.....  
State of..... Oregon....., I hereby certify that the within instrument was filed in this office  
for record on the 14 day of August, 1986  
Robert D. Budgett by.....  
(COUNTY OFFICIAL) (DEPUTY)