


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. J-9

History of original corner establishment:

The original corner was established by Aaron York under G.L.O. contract 309, dated July 12, 1879. His record reads:



Set Stone 30x20x4 for Cor to Secs. 8.9.16. and 17.  
Raised Stone Mound at Cor.

Description of corner evidence found:

Found stone 30x20x4 with 4 notches on one edge and 3 notches on a flat face. Stone was in a large stone mound.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set a 2" I.D. galvanized iron pipe 30" long with 2 1/2" brass cap 16" into the ground and stamped the cap as shown in diagram above. Buried the original stone under the monument. Placed a 3' diameter mound of stone around the monument and set a steel fence post 5' south of the monument with Forest Service Land Survey Monument and Property Boundary signs attached.

Scribed T8S R27E S9 BT on a 10" Juniper which bears N47° 35'E, 41.0'. Scribed T8S R27E S8 BT on a 11" Ponderosa Pine which bears N54° 55'W, 52.7'. Scribed T8S R27E S17 BT on a 12" Ponderosa Pine which bears S72° 07'W, 49.2'. Scribed T8S R27E S16 BT on a 8" Juniper which bears S60° 46'E, 95.0'. The bearings are true. Each scribe is in a 36" blaze. Nailed an aluminum washer, stamped RLS 852, between the letters B and T on each tree. Painted a 6" red band around the new bearing trees and attached Forest Service Land Survey Monument and Bearing Tree signs.

I certify the above corner point was perpetuated as hereon described on August 14, 1987.

REGISTERED PROFESSIONAL LAND SURVEYOR
---

*David L. Haddock*

OREGON JULY 12, 1968 DAVID L. HADDOCK 852
--

Office of Surveyor County of Grant  
 State of Oregon, I hereby certify that the within instrument was filed in this office  
 for record on the 27 day of Oct, 1987  
Robert D. Bayne by \_\_\_\_\_  
 (COUNTY OFFICIAL) (DEPUTY)