


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: Corner established in 1881 by F. W. Campbell under General Land Office Contract No. 380.



Surveyor General Reocrds (Notes) states:
Set a pine post for 1/4 Sec. Cor. from which
A tamarack 5 ins. diam. bears N14°W 25 lks.
A pine 24 in. diam. bears S80°E 31 lks.

(No subsequent remonumentations in county records)

Description of corner evidence found:

Found a 36-inch pine with scribing clearly visible bearing S80°E 20.5 ft. from corner position.

Description of monument and accessories established to perpetuate the original location of this corner

Set a 30 in. x 2 1/2 in. iron pipe with 3 in. brass cap marked as shown, 28 ins. in the ground for the 1/4 corner between Sections 2 & 3.

From which a new BT
A fir 12 ins. diam. bears S50°W 47.6 ft. marked T8S R31E 1/4S3 BT.

Distance taken to a brass washer in the blaze of the tree.


Set a steel fence post approximately 5 ft. North from corner with Forest Boundary sign attached.

Used steel tape and magnetic compass with declination = 20°E.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Douglas M. Ferguson

OREGON
JULY 12, 1938
DOUGLAS M. FERGUSON
848



Office of County Surveyor..... County of Grant.....
State of Oregon....., I hereby certify that the within instrument was filed in this office
for record on the 16 day of Nov., 1972 at 1 o'clock Pm., (signed)
Douglas M. Ferguson by
(COUNTY OFFICIAL) (DEPUTY)