


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: Corner established in 1881 by F. W. Campbell under General Land Office Contract No. 380.



Surveyor General Records (Notes) states:
Set a pine post for 1/4 Section Corner from which
A yellow pine 40 in. dia. bears S81°E 84 lks.
A yellow pine 10 in. dia. bears N86°W 20 lks.

(No subsequent remonumentations in county records)

Description of corner evidence found:

Found 44 in. snag with scribing visible.

Established corner position N81°W, 55.5 ft. from original Bearing Tree.

Description of monument and accessories established to perpetuate the original location of this corner

Set 30 in. x 2 1/2 in. iron pipe with 3 in. brass cap marked as shown, 25 in. in the ground for the 1/4 Sec. Cor. between Sections 1 & 2.

From which new BT's

A pine 18 in. diam. bears S4°E 50.9 ft. dist. marked T8S R31E 1/4S 1 BT.

A fir 8 in. diam. bears S69°W 18.3 ft. dist. marked T8S R31E 1/4S 2 BT.


Distances taken to a brass washer in the blaze of each tree.

Set a steel fence post approximately 5 ft. West from corner with Forest Boundary sign attached.

Used steel tape and magnetic compass with declination = 20°E.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Douglas M. Ferguson
OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848



Office of County Surveyor..... County of Grant.....
State of Oregon....., I hereby certify that the within instrument was filed in this office
for record on the 16 day of Nov., 1972, at 1 o'clock p.m., (signed)
Douglas M. Ferguson by
(COUNTY OFFICIAL) (DEPUTY)