


**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

**History of original corner establishment:** Corner established in 1881 by F. W. Campbell under General Land Office Contract No. 380.



Surveyor General Records (Notes) states:  
Set a basalt stone 18x15x4 and raised a mound of stone for 1/4 Sec. Cor. from which a pine 15 in. dia. bears S22°E 34 lks.

(No subsequent remonumentations in county records.)

**Description of corner evidence found:**

Found 18x15x4 in. basalt stone set in mound of stone with 1/4 marked on East face. From which a 25 in. juniper, live in good condition, with scribing clearly visible, bears S22°E 22.5 ft. dist.

Accepted stone as corner position.

**Description of monument and accessories established to perpetuate the original location of this corner**

Set 30 in. x 2 1/2 in. iron pipe with 3 in. brass cap marked as shown, 10 in. in the ground and raised a mound of stone around pipe 4 ft. at base x 20 in. in height, for the 1/4 corner between Sections 2 & 11.

From which a new BT  
A pine 16 in. diam. bears N30°W 53.5 ft. dist. marked T8S R31E 1/4 S 2 BT.

Distance taken to a brass washer in the blaze of the tree.  
Set a steel fence post approximately 5 ft. South from corner with Forest Boundary sign attached.

Used steel tape and magnetic compass with declination = 20°E.

**REGISTERED  
PROFESSIONAL  
LAND SURVEYOR**

*Douglas M. Ferguson*  
**OREGON  
JULY 12, 1968  
DOUGLAS M. FERGUSON  
848**

T.8S. R.31E  
1/4  
S2  
S.11  
1972  
PLS 848

Office of County Surveyor County of Grant  
State of Oregon, I hereby certify that the within instrument was filed in this office  
for record on the 16 day of Nov., 1972, at 1 o'clock p.m., (signed)  
*[Signature]* by *[Signature]*  
(COUNTY OFFICIAL) (DEPUTY)