CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner not previously established.

DIAGRAM

T8S R31E

C

S 1/16 S12

C

1980

PLS 848



Description of corner evidence found:

N.A.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 3"x30" galv iron pipe with 3" brass cap 22" in the ground & stamped brass cap as shown in diagram.
From which:
A pine 13" dia bears N 68-30 E, 53.9 ft. Scribed CS 1/16 S12 BT.
A pine 9" dia. bears S 2E 46.0 ft. " " " " "
Nailed brass washers stamped PLS 848 & bearing tree signs te each tree, painted red band around each tree.
Set steel posts 5'W & 5'N from corner with warning & bdry. signs.
Bearing-Solar Grid.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Witnesses to above corner

D. herburger

L. Wyllie

Office of Surveyor *County of* Grant
State of Oregon *, I hereby certify that the within instrument was filed in this office for record on the* 12 *day of* Jan *, 19*81
Robert D Bagett *by* .....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆GPO—798-276

H-23