


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

T.8S., R.31E., INDEX J.50-20

History of original corner establishment:

This corner was originally established by Douglas Ferguson as shown on Grant County Map of Survey No 599.



Description of corner evidence found:

Found a Brass capped monument and accessories as shown on Map of Survey No. 599. Due to the correction of certain corners as shown on Grant County Map of Survey No. 1707, the position of this corner is amended and a new monument is set.

Description of monument and accessories I establish to perpetuate the original location of this corner:

The position as determined by survey(See Map of Survey No. 1707) falls approx. 0.30 ft. into the SE face of a 10" juniper. Scribed said SE face "C-N-NE 1/64" and attached a brass washer stamped "PLS 848" in blaze face, from which:

- A Juniper(orig. BT.), 14" dia. bears S22°00'W, 2.0 ft., scribed C-N-NE 1/64 S14 BT
- A Juniper(orig. BT.), 14" dia. bears N18°00'W, 11.3 ft., scribed C-N-NE 1/64 S14 BT

The brass capped monument from Map of Survey 599 bears S87°59'26"W, 8.87 ft., Stamped "RM, 8.87" with arrow pointing toward new cap.

DIAGRAM

Painted red bands around BT's and painted blaze faces.
Placed Land Survey Monument signs and Bearing Tree tags on each BT.

No new monument set

Measurements to accessories taken with a magnetic compass, declination 20° East, and distances measured with nylon clad steel tape.

I hereby certify that the above corner point was perpetuated as shown hereon on June 5, 2003

Witness: D. Mitchell Ferguson, LSIT
David Herburger, Field Tech.

REGISTERED PROFESSIONAL LAND SURVEYOR



OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Office of County Surveyor _____ County of Grant
State of Oregon. I hereby certify that the within instrument was filed in this office for record on the 10 day of Aug, 2004

Robert R. Bennett by _____
County Surveyor Deputy

RENEWAL DATE:
01/01/2006